

Drawn cup roller bearing J-228-JTEKT - J-228-JTEKT

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/drawn-cup/j-228-jtekt>

Boundary dimensions



inch series, with cage assembly

| Bearing No. | Boundary dimensions(mm) | | | | Basic load ratings(kN) | | Fatigue load limit(kN) | | Limiting speeds(min-1) | |
|-------------|-------------------------|--------|------|--------|------------------------|-------|------------------------|-------------|------------------------|--|
| | Fw | D | C | Y(max) | Cr | CoR | Cu | Grease lub. | Oil lub. | |
| J-228 | 34.925 | 41.275 | 12.7 | 1.02 | 13.97 | 22.91 | 3.5 | 6000 | 9200 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3616060630315 |
| Inside diameter | 34.925 mm |
| Outside diameter | 41.275 mm |
| Thickness | 12.7 mm |
| Limiting speed | 6000 rpm |
| Weight | 29 g |
| Dynamic load | 13.97 kN |
| Static load | 22.91 kN |
| Packaging | - |
| Standard | No standard |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE