


## Needle roller cage K55-60-30-FH-JTEKT - K55-60-30-FH-JTEKT

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/cage/k55-60-30-fh-jtekt>

Boundary dimensions



Radial needle roller and cage assemblies

| Bearing No. | Boundary dimensions(mm) |    |    | Basic load ratings(kN) |     | Fatigue load limit(kN) | Limiting speed(r/min) |          |
|-------------|-------------------------|----|----|------------------------|-----|------------------------|-----------------------|----------|
|             | Fw                      | Ew | Bc | Ci                     | C0i | Ci                     | Grease lub.           | Oil lub. |
| K55X60X30FH | 55                      | 60 | 30 | 40.6                   | 103 | 16.1                   | 4900                  | 7600     |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3616060636027 |
| Inside diameter  | 55 mm         |
| Outside diameter | 60 mm         |
| Thickness        | 30 mm         |
| Limiting speed   | 4900 rpm      |
| Dynamic load     | 40.6 kN       |
| Static load      | 103 kN        |
| Packaging        | 1             |

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE