


Tapered roller bearing 368-362-JTEKT - 368-362-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/368-362-jtekt>

Single-row tapered roller bearings — Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a max.	<i>r</i> _b max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
50.800	88.900	20.638	22.225	16.613	1.6	1.2	74.3	87.3	4 400	5 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
368	362A	16.1	58.0	56.0	81.0	84.0	1.6	1.2	0.32	1.88	1.03	0.333	0.164

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427669
Inside diameter	50.8 mm
Outside diameter	88.9 mm
Thickness	20.638 mm
Packaging	1
Standard	No standard

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE