

## Tapered roller bearing 30230-JR-JTEKT - 30230R-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/30230r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>						
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.		Oil lub.					
150	270	49	45	38	483	664	1 300	1 800	30230JR					
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	Constant e	Axial load factors Y <sub>1</sub>	Axial load factors Y <sub>0</sub>	(Refer. 1) Mass (kg)	
4GB	52.4	168	175	256	234	255	9	11	3	2.5	0.44	1.38	0.76	11.6

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250258749
Inside diameter	150 mm
Outside diameter	270 mm
Thickness	49 mm
Weight	10500 g
Packaging	1
Standard	No standard

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE