


Drawn cup roller bearing BAM1422-IKO - BAM1422-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/drawn-cup/bam1422-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
22.225 (7/8)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring
F_w	D	C	B	Shaft dia. h_6		Housing bore dia. J_7		C	C_0	N	N_0	rpm	IRB 1022
22.225	28.575	34.92(1.375)	2.8	Max.	Min.	Max.	Min.	24 100	45 700	18 000			

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173177
Inside diameter	22.23 mm
Outside diameter	28.58 mm
Thickness	34.92 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE