


Drawn cup roller bearing BAM78-IKO - BAM78-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/drawn-cup/bam78-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
11.112 (7/16)	—	—	—	—	—	—	BAM 78	7	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	
F_w	D	C	h_8 Max.	J_7 Min.	Housing bore dia. Max. Min.	C N	C_0 N	rpm		
11.112 (7/16)	15.875 (5/8)	12.70 (500)	11.112	11.101	15.885 15.867	4 460	5 130	35 000	—	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173559
Inside diameter	11.11 mm
Inside diameter	7/16" inch
Outside diameter	15.88 mm
Outside diameter	5/8" inch
Thickness	12.7 mm
Thickness	1/2" inch
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE