


## Tapered roller bearing 30319-SKF - 30319-SKF

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/30319-skf>

Dimensions d'encadrement			Charges de base		Vitesses de base		Désignation
d	D	T	C	C <sub>0</sub>	Vitesse de référence	Vitesse limite	* Roulement SKF Explorer
mm			kN		tr/min		
95	200	49,5	330	390	2600	3400	30319



Technical drawing showing dimensions and load ratings for the tapered roller bearing 30319-SKF. The drawing includes dimensions for the inner diameter (d = 95 mm), outer diameter (D = 200 mm), and thickness (T = 49.5 mm). It also shows the dynamic load rating (C = 330 kN) and static load rating (C<sub>0</sub> = 390 kN). The reference speed is 2600 tr/min and the limiting speed is 3400 rpm. The drawing also shows the inner diameter of the inner ring (d<sub>i</sub> = 139 mm) and the outer diameter of the outer ring (D<sub>ext</sub> = 184 mm). The coefficient of calculation is given as Y<sub>0</sub> = 0.9.

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577005403
Inside diameter	95 mm
Outside diameter	200 mm
Thickness	49.5 mm
Limiting speed	3400 rpm
Weight	6540 g
Dynamic load	353 kN
Static load	390 kN
Packaging	1
Standard	No standard

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE