

Deep groove ball bearing single row 7215-BECBM-SKF - 7215-BECBM-SKF

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/single-row/7215-becbm-skf>

Dimensions d'encombrement			Charges de base		Vitesses de base		Désignation
d	D	B	dynamique C	statique C ₀	Vitesse de référence	Vitesse limite	* Roulement SKF Explorer
mm			kN		tr/min		
75	130	25	73,5	65,5	6300	8300	7215 BECBM

Technical drawing showing three views of the bearing: front view, side view, and cross-section. Dimensions include: D=130, B=25, d=75, r_{1,2} min 1,5, r_{1,2} max 1,5, e=98, D₂=85,3, d₂=84, D₁=121, D_{2max}=124, D_{1max}=121, r_{1,2} max 1,5, r_{1,2} min 1,5, e=98. Coefficients de calcul: i₀ 0,085, i₁ 1,4, e 1,14, k 0,36, Y 0,57, Y₀ 0,26.

PRODUCT FEATURES

Brand	SKF
N° Ean13	7316576633560
Inside diameter	75 mm
Sealing	Non-tight
Cage	Machined metal
Contact angle	40 °
Outside diameter	130 mm
Thickness	25 mm
Limiting speed	8000 rpm
Weight	1280 g
Dynamic load	73.5 kN
Static load	65.5 kN
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE