


## Tapered roller bearing 2580-2530-TIMKEN - 2580-2530-TIMKEN

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/2580-2530-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings					Part Number		
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
31.750	66.421	25.400	82700	0.27	21700	10200	2.14	94000	2580	2530
1.250	2.615	1.000	18500		4800	2200		21200		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage		Geometry Factors			kg					
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>		A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm					
25.267	26.636	-0.4	0.8	37.5	38.5	0.8	62.5	59.9	0.8	0.8	25.6	9.6	0.9006	0.41
0.9951	0.8125	-0.34	0.03	1.48	1.52	0.03	2.46	2.38	0.03	0.04				0.91

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952308524
Inside diameter	31.75 mm
Inside diameter	1 1/4" inch
Outside diameter	66.42 mm
Outside diameter	2.615" inch
Thickness	25.4 mm
Thickness	1" inch
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE